




EZ2050/EZ2150

Most affordable and powerful industrial barcode printers

The EZ2050 series is a perfect solution for industrial label printing applications where high performance and an affordable price is important.



Ethernet, Serial, USB port and Auto Calibration button included



Easy to change, low-cost printhead assembly



All metal, industrial enclosure and print mechanism



Free labeling software GoLabel for easy printing

Barcodes Made Easy

Model		EZ2050	EZ2150
Print Method		Thermal Transfer / Direct Thermal	
Resolution		203 dpi (8 dot/mm)	300 dpi (12 dots/mm)
Print Speed		6 IPS (150 mm/s)	4 IPS (102 mm/s)
Print Width		4.09" (104 mm)	
Print Length		Min. 0.16" (4 mm)** ; Max. 100" (2540 mm)	Min. 0.16" (4 mm)** ; Max. 45" (1143 mm)
Memory	Flash	8MB Flash (4MB for user storage)	
	SDRAM	16MB	
Sensor Type		Adjustable reflective sensor and transmissive sensor, left aligned	
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming	
	Width	Standard: 1" (25.4 mm) Min. - 4.64" (118 mm) Max. With Cutter: 4.61" (117 mm) Max. With Dispenser / Rewinder: 4.64" (118 mm) Max.	
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.25 mm) Max.	
	Label Roll Diameter	Max. 8" (203.2 mm) with 3" (76.2 mm) core / Max. 6" (152.4 mm) with 1.5" (38.1 mm) core	
Ribbon	Core Diameter	1.5" (38.1 mm) - 3" (76.2 mm)	
	Types	Wax, wax/resin, resin	
	Length	1471' (450 m)	
	Width	1.18" Min. - 4.33" (30 mm - 110 mm) Max.	
Printer Language	Label Design Software	EZPL, GEPL, GZPL auto switch	
	Driver	Windows 2000, XP, Vista, 7, Windows Server 2003 & 2008	
Software	DLL	Windows 2000, XP and Vista	
	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions	
Resident Fonts	Scalable Fonts	90°, 180°, 270° rotatable	
	Bitmap Fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable	
Download Fonts	Asian Fonts	90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions	
	Scalable Fonts	90°, 180°, 270° rotatable	
Barcodes	1-D Bar Codes	Code 39, Code 93, EAN 8 / 13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, and GS1 DataBar	
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code	
Code Pages		Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)	
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software	
Interfaces		Serial port: RS-232 (DB-9)	
		USB port Ethernet 10/100Mbps print server	
Control Panel		Three mono-color LED indicators: Power on, Ribbon out, Media out Control keys: FEED, PAUSE and CANCEL Calibration button	
Power		Auto Switching 100-240VAC, 50-60Hz	
Real Time Clock		Standard	
Environment	Operation Temperature	41°F to 104°F (5°C to 40°C)	
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)	
Humidity	Operation	30-85%, non-condensing	
	Storage	10-90%, non-condensing	
Agency Approvals		CE(EMC), FCC Class A, CB, cUL, CCC	
Dimension	Length	20.15" (512 mm)	
	Height	11.45" (291 mm)	
	Width	10.78" (274 mm)	
Weight		33 lbs (15 Kg), excluding consumables	
Options & Accessories		Cutter Module	
		Label Dispenser + Internal Rewinder	
		Parallel Port(IEEE1284)	
		Applicator Interface (1 input, 3 outputs, power 500mA @ 5V)	
		External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder	

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.
 ** Minimum print height specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc.
 Godex is pleased to test non-standard materials for minimum height printing capability.