



# HJW SERIES

## FEATURES

- 1/60000 Display Resolution(1/120000 Reserved)
- Providing Digital Filter Mechanism
- 24 Bit  $\Sigma$ - $\Delta$  High Speed A/D Converter With over 1,000,000 Internal Count
- Ideal for Laboratory and Jewelry Shops
- 6 x 19mm + 3 x 10mm Bold Type Wide Angle LCD Display Digits
- 13 User Programmable Weighing Units:-Metric, Metric Carat, Pound, Ounce, Dram, Grain (U.K.) ,Troy Ounce, Pennyweight, Momme(Japan), Tael(Taiwan), Tael(China), Troy Tael, Tola(India)
- User Friendly Operation
- Equipped with Initial Zero Tracking, Manual Zero Setting, Percentage Weighing, Counting Function, Smart Power Saving and Auto Calibration
- Dual Power Sources: Built-In Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 100 Hours Plus
- Low Battery Warning Signal
- See-through Easy Assemble Wind Shield
- Adjustable Feet, Back light, Bubble Level, Protection Cover, AC/DC Power Adaptor, RS232C Interface, Wind Shield (HJW-300&HJW-600) and Stainless Steel Platter Included



## SPECIFICATIONS

Model No.	HJW-300	HJW-600	HJW-1200	HJW-3000
Capacity	300g	600g	1200g	3000g
Readability	0.005g	0.01g	0.02g	0.05g
Repeatability (Std.dev)	0.005g	0.01g	0.02g	0.05g
Pan Size	ø110mm		140x170mm	
Wind Shield	YES		NO	
Tare Range	Full Tare Range(Subtractive)			
Power Source	By Built-In Rechargeable Battery or External Power Adaptor			
Operating Environment	10° ~ 35° C / 50° ~ 95° F Non-condensed.R.H.≤85%			
Individual Package	310 X 310 X 230 mm			
Net/Gross Weight	1.8kg/2.9kg (HJW-300,600) 2.2kg/3.3kg (HJW-1200,3000)			

Specifications subject to change without notice



unit=mm



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2<sup>nd</sup> Floor No.39 Pan Sheng Road Hsin Tien City 231 Taipei Hsin Taiwan R.O.C.  
Tel:886-2-29180121(12Lines) Fax : 886-2-29181508 ,29181652,29112176~7  
<http://www.uwe.com.tw> e-mail:uwe@ms8.jinet.net

