

# SERIES I10



## The newest mini I10 indicator



- OIML R76 Class III at single range and multirange operations.
- Wide angle 25 mm LCD weight display with bright backlighting.
- Programmable 2 function keys for easy and fast usage.
- 100 part counting memory for fast counting in high accuracy.
- 40 classifying memory with visual and acoustic annunciators.
- Animal weighing in high accuracy.
- Unit change function gives advantage for double unit operation.
- Serial data output for printer, remote display or PC connection.
- Optional second serial interface.
- Long time operation with rechargeable Li-ion battery.

## Specification

Model	I10
Range	Single range and multirange.
Display resolution	Up to 60,000 division.
Internal resolution	16,000,000 increment.
Stabilization time	Minimum 1.2 second, programmable.
Sampling quantity for part counting	10, 20, 30, 50, 100 pcs.
Memory size for part counting	100 different parts.
Classifying memory	40 different materials.
Totalization	2 separate accumulation memory for weighing and part counting.
Weighing units	g, kg, lb, oz.
Unit change	g – oz , kg – lb ( if programmed )
Clock	Programmable for dd.mm.yyyy, mm.dd.yyyy or yyyy.mm.dd.
Interface	RS232C. Optional second serial interface.
Air humidity	Max 90%
Protection	IP30
Enclosure material	ABS
Enclosure size(mm)	220 x 110 x 55
Battery	2000 mAh Li-ion battery ( optional ).
Power supply	100 – 230 VAC, 50-60 Hz / 12 VDC adaptor ( included ).

