



ADW

SERIES



WASHDOWN CHECKWEIGHER





COMMON FEATURES

- OIML-R76 and EC Class III Type Approved
- Washdown Construction: - Designed According to IP66
- Sealed Electronics
- Two Types of Display Version:
 - ADW-C = LCD Display
 - ADW-E = LED Display
- Support 1/6000 ~ 1/7500 Display Resolution for Non-OIML Applications*
- Support Metric and Avordupois Weight Units and Conversion
- User-Friendly Operation
- Weight Check Functions with:
 - HI-OK-LO Indicators and Buzzer Output
 - User-Programmable Buzzer Output Configuration
 - Automatic Tare Function
- Equipped with Power On Zero Tracking, Manual Zero and Auto Calibration Functions
- Protection Devices against Overload and Shock
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Completed with Low Battery and Charging Status Indicators
- Stainless Steel Platter Cover, Adjustable Feet, Built-in Rechargeable Battery, Power Adaptor and Bubble Level Included

* Display Resolution of Avordupois Weight Units always = 1/3000

Other Features Of LCD Display Version (ADW-C)

- Wide Angle LCD Display Digits
- Long Battery Operating Time: 120 Hours Plus
- Piece Counting Function

Other Features Of LED Display Version (ADW-E)

- Long Battery Operating Time: 80 Hours Plus
- Standby Indicator
- Smart Power Saving Function

OPTIONS AVAILABLE

- Rear Display
- Backlight (LCD Display Version Only)
- RS232C Interface

SPECIFICATIONS

Model No.	Capacity	Division	
		OIML	Non-OIML
ADW-1500C	1500g	0.5g	NIL
ADW-1500E			
ADW-3000C	3000g	1g	0.5g
ADW-3000E			
ADW-6000C	6000g	2g	1g
ADW-6000E			
ADW-15KC	15kg	0.005kg	0.002kg
ADW-15KE			
ADW-30KC	30kg	0.01kg	0.005kg
ADW-30KE			
Tare Range	Full Tare Range (Subtractive)		
Platter	215 x 250mm Stainless Steel		
Power Source	Built-in Rechargeable Battery or External AC/DC Power Adaptor		
Operation Environment	0°-40°C (32°-104°F), Non-condensed, R.H. ≤ 85%		

* Specifications subject in change without notice



UNIVERSAL WEIGHT ENTERPRISE CO., LTD.

2-5 Floor No. 39 Pao Shing Road Hsin Tien City 231 Taipei Hsin Taiwan R.O.C.
 Tel : +886-2-29187121 (12 Lines) Fax : +886-2-29181508 / 29183652 / 29112178-7
<http://www.uwe-scale.com.tw> e-mail: uwe@msb.hinet.net

