



AXM

SERIES

THE EXCELLENT WEIGHER



E C

FEATURES

- OIML-R76 and EC Class III Type Approved
- Support 1/6000 ~ 1/7500 Display Resolution for Non-OIML Applications
- Extended Display Function Provides 1/30000 Display Resolution when Required*
- Support Metric and Avoirdupois Weight Units and Conversion
- User Friendly Operation
- Equipped with Power On Zero Tracking, Manual Zero, Auto Calibration, Smart Power Saving and Automatic Tare Functions
- 5 1/2 x 25mm Oversize Wide Angle LCD Digits
- Protection Devices against Overload and Shock
- Dual Power Source: By Built-in Rechargeable Battery or Power Adaptor
- Long Battery Operating Time: 120 Hours Plus
- Completed with Low Battery and Charging Status Indicators
- Platter with Stainless Steel Insert, Adjustable Feet, Built-in Rechargeable Battery, Dust Cover, Power Adaptor and Bubble Level Included

* Extended Display Function does not support avoirdupois weight units

OPTIONS AVAILABLE

- Rear Display
- Backlight
- RS232C Interface
- All Stainless Steel Platter Cover

SPECIFICATIONS

Model No.	Capacity	Division		
		OIML	Non-OIML	Extended
AXM-1500	1500g	0.5g	0.2g	0.05g
AXM-3000	3000g	1g	0.5g	0.1g
AXM-6000	6000g	2g	1g	0.2g
AXM-15K	15kg	0.005kg	0.002kg	0.0005kg
AXM-30K	30kg	0.01kg	0.005kg	0.001kg
Tare Range	Full Tare Range (Subtractive)			
Platter	215 x 250mm with Stainless Steel Insert			
Power Source	Built-in Rechargeable Battery or External AC/DC Power Adaptor			
Operation Environment	0° ~ 40° C (32° ~ 104° F), Non-condensed. R.H. ≤ 85%			

* Specifications subject to change without notice



unit = mm